

**DESCRIPTION**

Design			Inlaid
Emboss			Calf
Thickness	EN 428	mm	2.25 ± 0.15
		inch	0.0885 ± 0.006
Weight	EN 430	kg/m <sup>2</sup>	2.60 ± 0.15
		oz/sq.Yd	77 ± 4
Roll width		cm	150 (-0 +1)
		inch	59 (-0 + 0.4)
Roll length		lm	24
		lyd	26 lyd 9 "

**PERFORMANCE**

Dimensional stability	EN 434 ASTM D 1204	%	≤ 0.2
Abrasion resistance	TABER ISO 9352	mg	250 ± 50
Static punch resistance	EN 433	mm	≤ 0.2
		inch	≤ 0.008
Low temperature resistance	D 42 1235 A	°C	- 20
Sound damping characteristics	ISO 717/2	dB	ΔI = 5
Colour fastness	ISO 877/76 ISO 4582/80 ASTM D 4459		≥ 7
Fire resistance	UTAC ST 18502/1		Type A
	ISO 3795/76	mm/mn	0
	FMVSS 302		Conform
	NF PA 253 ASTM E648	W/cm <sup>2</sup>	CRF > 0.50
	95/28/CE		Conform
Resistance to chemicals	EN 423	-	Unaffected by diluted acids and bases Unaffected by domestic products (excluding solvents for plasticized PVC)